

./translate5.sh log

```
/translate5.sh help log
```

Description:

Query the translate5 log

Usage:

log [options] [--] [<filter>]

Arguments:

filter Provide keywords to filter output. EXXXX is recognized as ecodes, text.text.text as domains and all other is searched in message. If keyword is only one Number, it is assumed that is a log ID and only that entry is shown.

Options:

-l, --level=LEVEL Filtering for specific level(s). If given as string, only the level given as string is shown. Given as integer: filtering for all levels as bitmask.
-f, --follow Show the most recent log entries, and continuously print new entries as they are appended to the log. Do not show a summary.
-a, --all Shows the full blown log data (extra, trace, etc)
-s, --since=SINCE Shows log data since the given pint int time (strtotime parsable string)
-u, --until=UNTIL Shows log data until the given pint int time (strtotime parsable string)
--no-summary Do not print the summary and intro texts - for further shell scripting.
--summary-only Print only the summary.
--purge Warning: purges the logs found by the given filters. Is asking for confirmation of not used with -q|--quiet or -n|--no-interaction.
-h, --help Display this help message
-q, --quiet Do not output any message
-V, --version Display this application version
--ansi Force ANSI output
--no-ansi Disable ANSI output
-n, --no-interaction Do not ask any interactive question
-v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Help:

Tool to query, investigate and purge the translate5 system log. By default a list of log entries and a summary is shown.

list output example:

2020-09-07 09:26:11 FATAL E1027 (#123) core PHP E_ERROR: Uncaught Error: Call to undefined method XYZ in foo.php:121

the format is:

log timestamp level ecode (#ID) app.domain message