

Term API

- [Create new term](#)
- [Create proposal for existing term](#)
- [Delete term](#)

Create new term	
Request	POST /editor/term
Params	collectionId Required . ID of TermCollection that new term should be created in See filterWindow.collections in Client app setup data response
	language Required . Rfc5646-code of a new term's language. See langAll[*].value in Client app setup data response
	term Required . Term text itself. String.
	note Required if runtimeOptions.termportal.commentAttributeMandatory config is On . String.
	termEntryId Optional . ID of termEntry, which new term should be attached under. If not given - new termEntry will be created.
Response	
<pre>{ "query": "test term", // Same as given by term-param "language": "5", // Language is returned as ID despite given as rfc5646 "collectionIds": "82", // Same as given by collectionId-param "termId": "607616", // ID of created term "termEntryId": "92182", // ID of created termEntry, or existing termEntry where new term was attached into "termTbxId": "id7657b259-6393-45fa-b53d-7e857d4882aa", "termEntryTbxId": "idaec78c6d-ea4b-46ab-bd84-9afa4070ecca" }</pre>	

Create proposal for existing term	
Request	PUT /editor/term
Params	termId Required . ID of existing term, for proposal to be created for
	proposal Optional . If not given, the existing proposal will be deleted, so existing term will be kept with no proposal
Response	
<pre>{ "updated": "Pavel Perminov, 06.05.2022 20:47:28 ", "proposal": "polig1", "processStatus": "unprocessed" }</pre>	

Delete term	
Request	DELETE /editor/term
Params	termId Required . ID of term to be deleted

Response contains isLast-property, indicating whether deleted term was the last having it's language, or last for the whole termEntry

Response

```
{
  "isLast": "(false|language|entry)",           // whether deleted term was the last within it's
language/entry
  "modified": "Pavel Perminov, 06.05.2022 20:59:07"
}
```