

Plug-In GlobalesePreTranslation: Globalese



If the API changes in an incompatible manner this is listed explicitly in the "important release notes" section of each [releases changelog](#).

The 'Globalese' pretranslation is triggered automatically on the translate5 import. The translate5 import will finish and the task will be available for usage after the Globalese pretranslation is done(the translated files are downloaded and merged).

Preconditions for the pretranslation to be started are:

- The Globalese Plug-In must be active
- the Globalese parameters must be sent to the server.

Save the 'Globalese' project parameters for later usage

URL:	editor/plugins_globalesepretranslation_globalese
Available Methods:	POST
Specialities:	The passed parameters will be saved internally, the 'Globalese' pretranslation process is triggered by event (importWorkerQueued) from the import workflow (task::post)

POST request parameters example(json):

```
{
  "engine": "globalese engine id",
  "group": "globalese group id",
  "apiUsername": "globalese username",
  "apiKey": "globalese api-key"
}
```

POST request layout

Name	Type	Info
engine	int	The id of the globalese engine
group	int	The id of the globalese group
apiUsername	string	The username used for globalese api authentication
apiKey	string	The apiKey used for globalese api authentication

Provides a list with all available groups.

URL:	editor/plugins_globalesepretranslation_globalese/groups
Available Methods:	GET
Specialities:	-

GET request parameters example (json):

```
{
  "username": "globalese username",
  "apiKey": "globalese api-key"
}
```

Groups request Layout

Name	Type	Info
username	string	The username used for globalese api authentication
apiKey	string	The apiKey used for globalese api authentication

Groups response Layout

Name	Type	Info
id	integer	The id of the group
name	string	The name of the group

Additional info: Only the groups who exist for the authenticated user will be returned.

Provides a list with all available engines.

URL:	editor/plugins_globalesepretranslation_globalese/engines
Available Methods:	GET
Specialities:	-

GET request parameters example (json):

```
{
  "username": "globalese username",
  "apiKey": "globalese api-key",
  "sourceLang": "5",
  "targetLang": "4"
}
```

Engines request Layout

Name	Type	Info
username	string	The username used for globalese api authentication
apiKey	string	The apiKey used for globalese api authentication

sourceLang	int	Source language id of the engine that will be searched
targetLang	int	Targed language id of the engine that will be searched

Engines response Layout

Name	Type	Info
source	string (rfc5646)	Source language of the engine
target	string (rfc5646)	Target language of the engine
group	int	The group id where this engine belongs to
id	int	The id of the engine
name	string	The name of the engine
status	string	The status of the engine ('on' or 'trained')