

Application Token

- [Creation of the token in the UI](#)
- [Creation of the token on CLI](#)
- [Usage of the token](#)
- [Administration](#)



Since 5.8.1 application tokens can be defined in translate5 and **MUST** be used for API usage.

Multiple tokens can be generated per each user.

Creation of the token in the UI

Your user must have the systemadmin or api role in order to get the APP token page.

Go to the App-Token administration (1) and (2) then add a new token (3) and follow the instructions.

translate5

Authenticated user: Project Manager
Login name: manager
Version: development (ext 6.2.0.981)
Browser: Chrome114Strict

Help All clients Logout

Projects Tasks Language resources Users Clients Preferences TermPortal InstantTranslate

Use for search Add Reload

Id	User	Description	Creation date	Expiration date
1	test, manager (testmanager)	Default	12/20/2022 18:40:16	
9	Manager, Project (manager)	Test token 1	12/22/2022 17:36:30	
11	Manager, Project (manager)	Test token 2	03/08/2023 23:15:50	07/20/2023
20	Manager, Project (manager)	Test token 3	07/17/2023 13:37:45	07/17/2023

My settings System configuration File format and segmentation settings Match ranges & pricing System Log System Check APP Tokens In-Context Fonts

Creation of the token on CLI

The creation is currently only possible over the Command Line interface - a UI implementation will probably follow. [For the usage of the CLI tools see the corresponding documentation.](#)

replace **LOGIN** and **DESCRIPTION** with appropriate values

```
./translate5.sh auth:apptoken:add LOGIN "DESCRIPTION"
```

See further documentation of the command see: [./translate5.sh auth:apptoken:add](#)



The token is shown only once! You have to copy it from where it is shown and store it where ever you want to use it!

Since it is stored encrypted in the translate5 DB it can not be retrieved anymore from translate5 again.

Usage of the token

The token can either be used as:

1. on session API endpoint login as password - instead of the normal password
2. As HTTP Header "Translate5AuthToken"
 - Each request with such header is authenticated - but gets a separate session

- For persist / keep session, just take the ZfExtended Cookie from the first call with the token and use that in further requests instead of the token itself
- or use the first option, the session API endpoint login and get the session id from there

Administration

A `./translate5.sh auth:apptoken:list` to show all tokens (the description only) for a user is planned, also a `./translate5.sh auth:apptoken:delete`.