

Plug-ins: Installation and activation

translate5 plug-ins can add major functionality to translate5 such as [Translation Memory](#), [Machine Translation](#), [conversion of native source files](#) (like Indesing, Word, etc.), Track Changes or Review in PDF-like layout.

To install a plug-in:

1. Place the plug-in folder inside of the plug-in directory of translate5, which is /application/modules/editor/Plugins - for many translate5 plug-ins this is already the case after installing translate5
2. Run the [translate5 updater](#)
3. Activate the plug-in in the configuration of translate5:
 - a. Open the table Zf_configuration in your translate5 database for editing
 - b. Search for the correct entry by using this SQL query: `SELECT * FROM `Zf_configuration` WHERE `name` LIKE 'runtimeOptions.plugins.active';`
 - c. Edit the field "value" and add your plugin in the existing listing:
 - i. Your existing listing may look like this:
["editor_Plugins_Transit_Bootstrap","editor_Plugins_TermTagger_Bootstrap","editor_Plugins_MatchResource_Init","editor_Plugins_ChangeLog_Init"]
 - ii. And after adding e. g. the Okapi plugin it will look like this
["editor_Plugins_Transit_Bootstrap","editor_Plugins_TermTagger_Bootstrap","editor_Plugins_MatchResource_Init","editor_Plugins_ChangeLog_Init","editor_Plugins_Okapi_Init"]
 - iii. Your new plug-in is active now.